



Graders G-2 Tubeless

Size	P.R.	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim	Load Capacity (kgs)	Inflation Pressure (Kpa)	Max.Speed
1300-24	16	1278	333	23.5	9.00DC	3000*6150	350*525	40km/h*10km/h
1300-24	12	1278	333	23.5	9.00DC	2725*5600	300*450	40km/h*10km/h
1400-24	12	1348	362	25	9.00DC	3075*6300	250*425	40km/h*10km/h
1400-24	16	1348	362	25	9.00DC	3650*7300	350*550	40km/h*10km/h



Excavator M-800 Tube Type

SIZE	PLY	Inflation Dimension (+/- 2%)		Rim	Inflation Pressure (+/- 15%) (Kpa)	Load Capacity (kgs)	
		Overall Diameter (mm)	Section Width (mm)			10km/h	50km/h
825-20	14	992	245	6.50	675	2400	1500
900-20	14	1030	260	7.00	700	4000	2500
1000-20	16	1062	280	7.50	750	5000	3000



Implement & Dumper M-880 Tubeless

SIZE	PLY	Inflation Dimension (+/- 2%)		Rim	Inflation Pressure (+/- 15%) (Kpa)	Load Capacity (kgs)	
		Overall Diameter (mm)	Section Width (mm)			10km/h	50km/h
405/70-20	14	1076	407	13.00	350	5300	3250
405/70-24	14	1178	407	13.00	350	5800	3550



Multi-Purpose Truck M-900 Tube Type

SIZE	PLY	Inflation Dimension (+/- 2%)		Rim	Inflation Pressure (+/- 15%) (Kpa)	Load Capacity (kgs)	
		Overall Diameter (mm)	Section Width (mm)			10km/h	50km/h
16/70-20	14	1076	407	13.00	350	5300	3250





Farm Front F-2 Tube Type

Size	P.R.	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim	Load Capacity (kgs)	Inflation Pressure (Kpa)
4.00-19	4	712	112	11	3.00D	355	340
5.00-15	4	655	140	13	4.00E	365	280
5.50-16	6	710	150	15	4.00E	530	370
6.00-16	6	735	165	16	4.50E	560	330
6.00-19	6	814	165	16	4.50E	650	330
6.50-16	6	760	175	17.5	4.50E	615	310
7.50-16	8	805	205	20	5.50F	875	370
7.50-18	8	860	205	20	5.50F	950	370
9.00-16	10	855	234	23	6.00F	1250	390
10.00-16	10	895	274	26	W8	1360	340
11.00-16	10	965	315	29	W10L	1500	310



Loader Backhoe, also suitable for Implement and Trailer F-3 tubeless

Size	P.R.	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim	Load Capacity (kgs)	Inflation Pressure (Kpa)
11L-16	12	838	279	12	8LB	1250	440



IMPLEMENT & TRAILER F-600 Tubeless

SIZE	PLY	Inflation Dimension(+/- 2%)		Rim	Inflation (+/- 15%) (Kpa)	Loading Capacity 40km/h (kgs) Free Rolling (LLV)
		Overall Diameter (mm)	Section Width (mm)			
10.0/80-12	8	710	264	9.00	310	1250
10.0/80-12	10	710	264	9.00	390	1440
10.0/75-15.3	10	760	264	9.00	390	1550
10.0/75-15.3	12	760	264	9.00	470	1700
10.0/75-15.3	14	760	264	9.00	550	1900
11.5/80-15.3	10	845	290	9.00	340	1950
11.5/80-15.3	12	845	290	9.00	410	2180
11.5/80-15.3	14	845	290	9.00	475	2430
12.5/80-15.3	14	889	307	9.00	430	2650
12.5/80-15.3	16	889	307	9.00	490	2820
13.0/65-18	14	890	336	11.00	430	2575
13.0/65-18	16	890	336	11.00	490	2800





Super Deep Traction & Strong Sidewalls (Rim Guard)

Industrial Tires S-800

Size	P.R.	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rims	Inflated		Load Capacity (kgs)						
						Pressure (Kpa)	Drive Wheel		Steer Wheel		Industrial Vehicles			
							16km/h	24km/h	24km/h	32km/h	8km/h	16km/h	24km/h	32km/h
5.00-8	10	468	144	12	3.50D	1000	1290	1100	955	850	955	760	705	655
6.00-9	10	540	166	13	4.00E	860	1680	1515	1280	1125	1280	1010	945	875
6.50-10	10	590	186	15	5.00F	790	1915	1725	1455	1280	1455	1150	1075	1000
7.00-12	12	676	197	19	5.00S	860	2720	2445	2065	1815	2065	1360	1520	1415
7.00-12	14	676	197	19	5.00S	1000	2965	2670	2255	1980	2255	1780	1660	1540
7.00-15	12	762	203	19	5.50F	860	3150	2835	2395	2100	2395	1890	1760	1635
7.00-15	14	762	203	19	5.50F	1000	3400	3060	2585	2270	2585	2040	1910	1785
7.50-15	12	802	215	19	6.00G	790	3490	3140	2650	2330	2650	2095	1955	1815
7.50-15	14	802	215	19	6.00G	925	3640	3290	2800	2480	2800	2245	2105	1965
8.25-15	12	830	250	20	6.5	720	3935	3545	2990	2630	2990	2365	2205	2050
8.25-15	14	830	250	20	6.5	830	4255	3830	3235	2845	3235	2555	2365	2215
18x7-8	14	465	173	14	4.33R	900	1855	1685	1450	1295	1450	1160	1100	1040
18x7-8	16	465	173	14	4.33R	1000	2130	1960	1640	1490	1640	1355	1285	1205
21x8-9	14	533	203	15	6.00E	1000	2350	2115	1785	1570	1785	1405	1315	1220
23x9-10	18	584	225	13	6.50F	1080	3240	2900	2485	2285	2485	1965	1875	1710
23x10-12	12	597	255	14	8	830	3290	2950	2495	2185	2495	1970	1835	1705
27x10-12	14	690	255	16	8.00G	830	3400	3035	2650	2350	2650	2140	1980	1800
28x9-15	14	706	231	20	7	970	3415	3075	2595	2280	2595	2050	1910	1775
250-15	16	735	250	20	7.5	930	4285	3855	3265	2860	3265	2575	2405	2230
250-15	18	735	250	20	7.5	1030	4580	4105	3470	3040	3470	2745	2560	2375
300-15	20	840	300	21	8	930	6575	5940	4990	4400	4990	3945	3675	3425
9.00-20	14	1034	259	20	7	760	5880	5285	4465	4105	4465	3520	3290	3065
10.00-20	16	1070	278	22	7.5	795	6765	6085	5140	4520	5140	4055	3790	3520
10.00-20	18	1070	278	22	7.5	900	7300	6560	5545	4875	5545	4370	4090	3800
12.00-20	16	1145	315	25	8.5	680	7725	6980	5895	5180	5895	4655	4345	4035
12.00-20	18	1145	315	25	8.5	900	8275	7500	6415	5700	6415	5175	4865	4555
12.00-20	24	1145	315	25	8.5	1150	9455	8680	7595	6880	7595	6355	6045	5735
12.00-20	28	1145	315	25	8.5	1300	10355	9460	8345	7630	8345	7105	6795	6485





Aerial Lifts S-200 tubeless

Size	P.R.	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim	Load Capacity (kgs)	Inflation Pressure (Kpa)
385/65-22.5	16	1092	394	20.5	11.75	5580	690
36x14-22.5	14	914	338	20.5	11.75	4935	630
39x15-22.5	14	978	381	20.5	12.25	4070	735



All Terrains Forklifts RF-1 tubeless

Size	P.R.	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim	Load Capacity (kgs)	Inflation Pressure (Kpa)
29x12.5-15	10	742	310		10	1200	410



All Terrains Forklifts S-600 tubeless

Size	P.R.	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim	Load Capacity (kgs)	Inflation Pressure (Kpa)
31.5x13-16.5	12	795	330	19	9.75	2435	480
26x12-12	12	648	307	22	10.50	1735	520



Skidsteer S-600 Premium (Rim Guard) tubeless

Size	P.R.	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Rim	Load Capacity (kgs)	Inflation Pressure (Kpa)
10-16.5	8	773	264	19	8.25	1880	410
10-16.5	10	773	264	19	8.25	2135	520
12-16.5	10	831	307	19	9.75	2540	450
12-16.5	12	831	307	19	9.75	2865	550
27x8.5-15	6	678	213	13	7JA	1030	310
14-17.5	14	921	349	19	10.5	3875	550
15-19.5	14	1019	389	21	11.75	4565	485

